


Standard Bridge Submarine Cable

XLPE insulation / 22 AWG to 1000 KCMIL / dual HDPE jackets / 600 and 2000 volt



Application

These are multi-conductor 600 and 2000 volt cables designed for underwater usage and meet all requirements for use on bascule, lift and swing-bridges as well as direct burial. They are produced to meet your specific combination of power, control and signal circuits (including fiber optic components) of up to 125 conductors and up to 5 inches (12.7 cm) in diameter. Empty conduit may also be cabled in as an integral part of the cable.

These cables have evolved over our long relationship with architectural/engineering firms and the US Departments Of Transportation (DOT). They are designed to perform flawlessly under the harshest of conditions.

The features listed below are standard items; they may be modified per your request and need. Please contact Draka for details.

Specifications and Ratings

- ICEA S-95-658, NEMA WC-70
- ICEA S-73-532, NEMA WC-57
- BIW Specifying Standard SC-02

Design Parameters

CONDUCTOR: Annealed uncoated copper to meet ASTM B-3, stranded to meet ASTM B-8, class B stranding, and ICEA S-95-658, NEMA WC-70.

INSULATION: Crosslinked polyethylene (XLPE) meeting ICEA S-95-658, NEMA WC-70. The insulation meets accelerated water absorption per Electrical Method EM-60. Insulation thickness for 600V and 2000V shall comply with ICEA standards.

CIRCUIT IDENTIFICATION: Surface printed legend with number/color (1-BLACK, 2-WHITE, 3-RED, etc.) per ICEA S-73-532, NEMA WC-57-1990, Appendix E, Method 4.

ASSEMBLY: Cable components are cabled together with polypropylene as required by the application. The cabled core is wrapped with a moisture-resistant binder tape. Lay length and directions conform to ICEA S-95-658, NEMA WC70.

INNER JACKET: Weather and UV-resistant high density polyethylene (HDPE) per ICEA S-95-658, NEMA WC-70. Jacket thickness varies per cable diameter; see chart on back.

ARMOR WIRE: Galvanized steel wire coated with HDPE per ICEA S-95-658, NEMA WC-70. Coating thickness is shown on back.

OUTER JACKET: Weather and UV-resistant high density polyethylene (HDPE) per ICEA S-95-658, NEMA WC-70. Jacket thickness varies per cable diameter; see chart on back.

Prysmian Group

700 Industrial Drive | Lexington, SC 29072 | +1-800-845-8507 | www.prysmiangroup.com

Sales and Distribution:

22 Joseph E. Warner Blvd. | North Dighton, MA 02764 | +1-508-822-5444 | www.drakausa.com
One Tamaqua Blvd. | Schuylkill Haven PA 17972 | Tel +1-570-385-4381

Standard Bridge Submarine Cable

XLPE insulation / 22 AWG to 1000 KCMIL / dual HDPE jackets / 600 and 2000 volt

Calculated Cable Diameter Under Jacket in (mm)	Inner Jacket Thickness in (mm)	Armor Wire Size BWG in (mm)	Armor Wire Coating in (mm)	Outer Jacket Thickness in (mm)
0 to 0.425 (10.8)	.045 (1.1)	12 .109 (2.8)	.020 (0.51)	.045 (1.1)
0.426 (10.8) to 0.700 (17.8)	.060 (1.5)	10 .134 (3.4)	.025 (0.64)	.060 (1.5)
0.701 (17.8) to 1.500 (38.1)	.080 (2.0)	8 .165 (4.2)	.030 (0.76)	.080 (2.0)
1.501 (38.1) to 2.500 (63.5)	.110 (2.8)	6 .203 (5.2)	.035 (0.89)	.110 (2.8)
2.501 (63.5) and Larger	.140 (3.6)	4 .238 (6.0)	.040 (1.02)	.140 (3.6)

The data herein is approximate and subject to normal manufacturing tolerances.

Information is subject to change without notice. Consult factory for a variety of alternate constructions for specific applications.

Prysmian Group

700 Industrial Drive | Lexington, SC 29072 | +1-800-845-8507 | www.prysmiangroup.com

Sales and Distribution:

22 Joseph E. Warner Blvd. | North Dighton, MA 02764 | +1-508-822-5444 | www.drakausa.com

One Tamaqua Blvd. | Schuylkill Haven PA 17972 | Tel +1-570-385-4381