

600 Volt TYPE XHHW-2

Low Voltage Building Wire



Description

Single copper or aluminum Series 8000 conductor with 600 Volt, XLPE insulation.

Specifications

UL- UL 44

FED- Federal Specification JC-30B

ICEA- ICEA S-95-658

For 90°C Wet or Dry Operation.

Ratings

XHHW-2
Sunlight Resistant

Design Parameters

CONDUCTOR: Single conductor, Class B concentric compressed stranded annealed copper or Class B concentric compact aluminum Series 8000 per ASTM.

INSULATION: High quality, tough, heat resistant, and moisture resistant, thermosetting cross-linked polyethylene insulation.

Options

- VW-1
- Compact Copper Conductor
- Compressed Aluminum Conductor
- CT Rated (1/0 AWG and Larger)

Installations



Conduit in Air



Wet Locations



Industrial




Isolated in Air



Dry Locations

600 Volt TYPE XHHW-2

Low Voltage Building Wire



Product Number	Conductor	Insulation Thickness (mils)	Conductor Diameter (in.)		Overall Diameter (in.)	Cable Weight (lbs/1000ft)	† Ampacity (Amps)	
			(A)	(B)			Raceway	In Free Air
600 Volt Copper								
5 Q00810A	8 AWG CU	45	0.143	0.24	64	55	80	
5 Q01810A	6 AWG CU	45	0.180	0.27	96	75	105	
5 Q02810A	4 AWG CU	45	0.226	0.32	147	95	140	
5 QYZ034A	3 AWG CU	45	0.253	0.35	183	115	165	
5 Q03810A	2 AWG CU	45	0.284	0.38	228	130	190	
5 Q06810A	1 AWG CU	55	0.324	0.44	289	145	220	
5 Q08810A	1/0 AWG CU	55	0.364	0.48	361	170	260	
5 Q09810A	2/0 AWG CU	55	0.408	0.53	449	195	300	
5 Q0A810A	3/0 AWG CU	55	0.458	0.58	560	225	350	
5 Q0B810A	4/0 AWG CU	55	0.515	0.63	700	260	405	
5 Q0C810A	250 MCM CU	65	0.561	0.70	829	290	455	
5 QYZ035A	300 MCM CU	65	0.614	0.75	988	320	500	
5 Q0D810A	350 MCM CU	65	0.664	0.80	1147	350	570	
5 QYZ036A	400 MCM CU	65	0.710	0.85	1312	380	615	
5 Q0E810A	500 MCM CU	65	0.794	0.94	1620	430	700	
5 QYZ037A	600 MCM CU	80	0.870	1.04	1958	475	780	
5 Q0F810A	750 MCM CU	80	0.974	1.15	2444	535	885	
Q0G810A	1000 MCM CU	80	1.124	1.29	3273	615	1055	

PRODUCT NOTES:

5 Items are Prysmian authorized stock. The above dimensions are approximate and subject to normal manufacturing tolerances.


† Ampacities are based on the following:

In Raceway 2011 NEC Table 310.15(B)(16):
Not more than three current-carrying conductors, 90°C conductor temperature, and 30°C ambient temperature.

In Free Air 2011 NEC Table 310.15(B)(17):
Single-insulated conductor, 90°C conductor temperature, and 30°C ambient temperature.

600 Volt TYPE XHHW-2

Low Voltage Building Wire



Product Number	Conductor	Insulation Thickness (mils)	Conductor Diameter (in.)		Overall Diameter (in.)	Cable Weight (lbs./Kft)	† Ampacity (Amps)	
			(A)	(B)			Raceway	In Free Air
600 Volt Series 8000 Aluminum								
⁵ QOJ818A	6 AWG AL	45	0.171	0.27	39	55	85	
⁵ QOK818A	4 AWG AL	45	0.215	0.32	59	75	115	
⁵ QOM818A	2 AWG AL	45	0.266	0.37	86	100	150	
⁵ QOO818A	1 AWG AL	55	0.299	0.42	112	115	175	
⁵ QOQ818A	1/0 AWG AL	55	0.336	0.46	135	135	205	
⁵ QOR818A	2/0 AWG AL	55	0.379	0.50	164	150	235	
⁵ QOS818A	3/0 AWG AL	55	0.423	0.55	203	175	275	
⁵ QOT818A	4/0 AWG AL	55	0.479	0.60	246	205	315	
⁵ QOU818A	250 MCM AL	65	0.520	0.66	298	230	355	
⁵ QYZ030A	300 MCM AL	65	0.570	0.71	345	260	395	
⁵ QOV818A	350 MCM AL	65	0.622	0.76	398	280	445	
⁵ QYZ031A	400 MCM AL	65	0.659	0.80	449	305	480	
⁵ QOW818A	500 MCM AL	65	0.742	0.88	552	350	545	
⁵ QYZ032A	600 MCM AL	80	0.813	0.99	681	385	615	
⁵ QYZ033A	700 MCM AL	80	0.877	1.05	783	425	670	
⁵ QOX818A	750 MCM AL	80	0.917	1.09	824	435	700	
307419A	900 MCM AL	80	1.009	1.18	960	480	790	
QOY818A	1000 MCM AL	80	1.071	1.24	1074	500	845	

PRODUCT NOTES:

⁵ Items are Prysmian authorized stock. The above dimensions are approximate and subject to normal manufacturing tolerances.

† Ampacities are based on the following:

In Raceway 2011 NEC Table 310.15(B)(16):
Not more than three current-carrying conductors, 90°C conductor temperature, and 30°C ambient temperature.

In Free Air 2011 NEC Table 310.15(B)(17):
Single-insulated conductor, 90°C conductor temperature, and 30°C ambient temperature.